# **Product datasheet**

Specifications





# SpaceLogic KNX Switch/Blind Extension 8ch 10AX/16AC1

MTN6805-0008

#### Main

Range Of Product	SpaceLogic KNX
Product Or Component Type	Combined blind relay
Operating Mode	KNX bus system
Bus Type	KNX
Rated Input	ON/OFF status:

## Complementary

Mounting Support	DIN rail
[Ue] Rated Operational Voltage	250 V AC 50/60 Hz
[In] Rated Current	16 A 10 A
Number Of Outputs	8 4

#### Environment

Ip Degree Of Protection	IP20
-------------------------	------

## **Packing Units**

	PCE
Number Of Units In Package 1	1
Package 1 Height	7.700 cm
Package 1 Width	12.400 cm
Package 1 Length	15.700 cm
Package 1 Weight	369.000 g
Unit Type Of Package 2	S04
Number Of Units In Package 2	24
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	9.596 kg

# 

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.



Transparency RoHS/REACh

#### Well-being performance

Mercury Free

Rohs Exemption Information Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information